

Precast Concrete Sinks



APPLICATIONS & BENEFITS

At Living Concrete, we specialise in crafting bespoke precast concrete sinks that are both functional and stylish, perfect for a range of commercial spaces. Whether for restaurants, bars, pubs, hotels, or any other hospitality or commercial venues, our custom-designed concrete sinks are tailored to meet the unique aesthetic and practical needs of your project. Each sink is a seamless blend of design and durability, offering a striking yet robust solution for high-use environments.


Our precast sinks are made using BTX Ultra High-Performance Glass Reinforced Concrete (GRC), produced in the UK with a low environmental impact. By sourcing raw materials locally and employing eco-conscious production practices, we minimize our carbon footprint, ensuring that sustainability is built into every product.

Living Concrete holds both Environmental Product Declarations (EPDs) and ISO 14001 Environmental Management System certifications, underscoring our commitment to environmentally responsible design.




AVAILABLE SIZES


Sense Washbasin without Tap Hole




600 x 400 x 100 mm




600 x 400 x 210 mm




800 x 400 x 100 mm




800 x 400 x 210 mm




Sense Washbasin with Tap Hole




600 x 440 x 100 mm




600 x 440 x 210 mm



800 x 440 x 100 mm



800 x 440 x 210 mm



Fittings: Taps or waste fittings are **NOT** included.

TEXTURES & FINISHES



Silk (Smooth)

All our washbasins are impregnated and protected by an invisible hydrophobic agent, limiting the absorption of water and protecting against moisture. The impregnation forms a transparent film on the surface of the concrete. The protected surface becomes more resistant to mechanical and chemical damage and easier to clean. It may change the colour and give the surface a gloss finish.

AVAILABLE COLOURS

Colour Variations: Because of its cementitious composition the colour of GRC sinks may have different textures and tones in comparison to other washbasins in the same batch. The colours in our colour selection chart are for reference use only and are as close as possible to the original colours.



MECHANICAL PROPERTIES

Yield strength (modulus of rupture)	5-8 mpa
Tensile strength (modulus of rupture)	2-5 mpa
Compressive strength	20-30 mpa
Impact strength	5-10 KJ/m ²
Thermal expansion coefficient	20 x 10 ⁻⁶ /°C
Absorption	Low water permeability
Dorry wear	2.5 mm

TOLLERANCES

Thickness	+/-5%
Side straightness	+/-0.5%
Orthogonality	+/-0.6%
Planimetry	+/-0.5%
Length and width	+/-0.6%

NOTE: These values are for reference only and are estimated as formulation. They may vary according to formulation, treatment and manufacturing processes.

Care and Maintenance: Instructions are supplied with each washbasin; we strongly advise familiarizing yourself with the nature of the concrete material and cleaning processes required to maintain your product.

PRODUCT INFORMATION

STORAGE

- Keep in a dry, clean space in the original packaging
- Washbasins should be stored horizontally

CLEANING AND MAINTENANCE

- Clean with neutral pH detergent
- Use wax maintainers or self-polishing cleaners
- To clean specific stains do not use abrasive materials
- Do not leave stains to dry, as they may permanently stain the surface
- For outdoor apply sealant periodically depending on usage
- Sweep the surface regularly to remove all dirt and dust

COLOUR VARIATIONS

Because of its cementitious composition the colour of GRC washbasins may have different textures and tones within the same batch and / or in comparison to other washbasins in the same consignment. Our colour selection chart is for reference use only and the colours are as close as possible to the original colours.

VERIFICATION OF THE AESTHETIC APPEARANCE

Please check and ensure that you are happy with the delivered product and there is no apparent visible defects. If any issues are detected do not start the installation and contact supplier immediately. No claims will be accepted after tiles have been installed.